



C1 LED Ceiling Spot Light

The new Major Tech LED flush ceiling mount fixtures are the perfect way to bring light, character, and a modern look to your space. These white recessed and swivel LED COB ceiling spot lights with the beehive aluminum reflector provides a perfect light very similar to halogen dichroic bulbs. This range has a 40° beam angle and is supplied in 3W, 5W, 7W and 10W versions, with the option of dimmable models. The 10W models are ideal for restaurants, hotels, schools and hospitals. The dimmable versions equipped with the dimmable module. This range is perfect for new installations or where retrofit of old halogen lamps is required. These lights are ideal for homes, offices, hotels, shops, restaurants, etc.

Features :

- Recessed and swivel LED ceiling light
- White painted aluminum frame with decorative black swivel ring
- Easy to install with two spring clips
- High quality Chinese COB inside, high performance and economic cost
- Integrated design with LED and housing combined
- Narrow cut-off reflector creates visual comfort, and generates medium beam with glare cut off angle 40°
- Available in dimmable or non-dimmable versions
- Available in Warm White 3000k and Cool White 6000k
- Creta driver included

Application:

- Home lighting, hotels, commercial lighting, shop lighting and conference venues
- Perfect for living rooms, kitchens, bathrooms, bedrooms and passages
- Recessed lights are also used to create shadowing of objects while adding texture to vertical surfaces.



节能高达 90%
Energy saving up to



PART NO. NON DIMMABLE	PART NO. DIMMABLE	LED POWER	LED COLOUR	COLOUR TEMP	LUMEN lm	LAMP SIZE (MM)	HOLE CUT OUT SIZE	BEAM ANGLE	WORKING VOLTAGE	PROTECTION GRADE	MATERIAL
C1-3WC	C1-D3WC	3W	Cool White	6000K	255 lm	90mm Ø x 35mm H	70mm	40°	AC85-265V	IP20	AL+LN
C1-3W	C1-D3W	3W	Warm White	3000K	255 lm	90mm Ø x 35mm H	70mm	40°	AC85-265V	IP20	AL+LN
C1-5WC	C1-D5WC	5W	Cool White	6000K	425 lm	90mm Ø x 35mm H	70mm	40°	AC85-265V	IP20	AL+LN
C1-5W	C1-D5W	5W	Warm White	3000K	425 lm	90mm Ø x 35mm H	70mm	40°	AC85-265V	IP20	AL+LN
C1-7WC	C1-D7WC	7W	Cool White	6000K	595 lm	100mm Ø x 50mm H	80mm	40°	AC85-265V	IP20	AL+LN
C1-7W	C1-D7W	7W	Warm White	3000K	595 lm	100mm Ø x 50mm H	80mm	40°	AC85-265V	IP20	AL+LN
C1-10WC	C1-D10WC	10W	Cool White	6000K	850 lm	100mm Ø x 70mm H	80mm	40°	AC85-265V	IP20	AL+LN
C1-10W	C1-D10W	10W	Warm White	3000K	850 lm	100mm Ø x 70mm H	80mm	40°	AC85-265V	IP20	AL+LN