

شركة البدرى للإضاءة المتخصصة

إحدى شركات مجموعة البدرى للتنمية والاستثمار

BADRY Lighting Professionals' Co

DMX Lighting Control Board

D.M.X Lighting Control Console

Model Type. DMX Control Board

Model No. ST-65354

Stock / Part No. MFR # 65354

Item Brand. Strand Lighting

Lighting 500ML Lighting Control Console

Item Specifics

- 4 Universes, 2048 DMX Channels
- 8" TFT Color Touchscreen
- 119 Backlit Keys, Four Rotary Encoders
- 24 Faders, One Level Wheel
- Four DMX Outputs
- DVI External Monitor Output
- Supports Up To 500 Cue Lists of 500 Cues
- CE Marked

Item description



The 500ML Lighting Control Console from Strand Lighting is designed to operate dimmers, LED fixtures, and moving lights. The 8" TFT color touchscreen allows for fast set up, while backlit command buttons make it easy to use. The unit has one external DVI port to add a touch monitor for more control.

In addition, the 500ML console features four universes for a total of 2048 channels, and 24 faders.

Each may be used as a Master, Sub Master, or as a Playback control. Equipped with backlit Play, Pause/Reverse, and Bump buttons, they allow cue stacks to be triggered as required. Using industry standard methods of control, the user interface is easy to learn, allowing the operation to appeal both to the casual and professional operator alike.

LCD fader bank information screens

Supports 3-pin XLR desk lamps

CE marked





إحدى شركات مجموعة البدرى للتنمية والاستثمار

BADRY Lighting Professionals' Co

Technical parameters

Control	2048 DMX channels, 4 universes
	1 x RJ45, Ethernet
Connectivity	2 x USB 2.0, front
	1 x USB 2.0, rear
	1 x DVI, monitor output
	4 x DMX outputs
	1 x MIDI input
	1 x MIDI output
	1 x MIDI pass-thru
	1 x SMPTE input
	1 x 3-pin XLR
	119 x Backlit keys
	4 x Rotary encoders
	24 x Faders
Controls	1 x Level wheel
Display	8" TFT color touchscreen
1 2	
Power	Universal power supply, 100 to 240 VAC
	CE marked, ETL listed with cULus listed power
Approvals	supply, C-Tick
	Divid folded about steel and flows notendant ADS
Construction	Rigid folded sheet steel and flame-retardant ABS controls
Operating	
Temperature	32 to 104° F / 0 to 40° C

6B, Sixth October St., Manshiat Al Sad Al Aaly Al-Salam - Cairo - Egypt. Tel : +202 229 585 30 - 229 554 87 Fax : +202 229 958 60

www.badrygroup.com Lighting@badrygroup.com



شركة البدرى للإضاءة المتخصصة

إحدى شركات مجموعة البدرى للتنمية والاستثمار

BADRY Lighting Professionals' Co

Storage Temperature	32 to 95°F / 0 to 35°C
Humidity	0 to 95%
Dimensions	25.9 x 19.3 x 12.1" / 65.7 x 48.9 x 30.8 cm
Weight	45.1 lb / 20.5 kg

Warranty

We offer 2 years warranty

6B, Sixth October St., Manshiat Al Sad Al Aaly, Al-Salam - Cairo - Egypt. Tel : +202 229 585 30 - 229 554 87 Fax : +202 229 958 60

www.badrygroup.com Lighting@badrygroup.com ٦ب ش٦أكتوبر من جسر السويس – القاهرة – الدور الثالث – شقه ٥ منشية السد العالي – السلام – القاهرة – مصر ت: ٢٢٩٥٨٥٣٠ – ٢٢٩٥٥٤٨٧ ف: ٢٢٩٩٥٨٦٠